

**icontrol·lite**  
(C4R+)

Inspection Rewinder



The **icontrol Lite** (also named **C4R+**) is a Inspection slitter rewinder and offer the following features :

- Slit with large choice of slitting solutions
- Inspect, by using cells or 100% inspection camera, and stop defects on a splicing table,
- Rewind rolls, on a single shaft, dual shafts or with a semi automatic turret rewriter, with a pre-selected length or number of labels.

**Technical specifications**

|                                   |                   |
|-----------------------------------|-------------------|
| Available web width's             | 350 mm and 420 mm |
| Maximum unwind roll diameter      | 800 mm            |
| Maximum rewinding diameter's :    |                   |
| Single rewind shaft               | 500 mm            |
| Two mandrels "Alternate Mode"     | 500 mm            |
| Two mandrels "Simultaneous Mode"  | 300 mm            |
| Maximum number of slitting blades | 10 maxi           |
| Minimum distance between blades   | 12 mm             |
| Electrical Requirements           | 4 KW tri 400      |
| Compressed Air Requirements       | 6 bars            |
| Total Length                      | 2 100 mm          |
| Total Width                       | 1 200 mm          |
| Total Height                      | 1 700 mm          |
| Weight                            | 500 kg            |
| Maximum Web Speed                 | 250 m/min         |